

EnhanceLite™ PAR20

High output, PAR20 LED Lamp



EnhanceLite® PAR20

Key Product Features

- High output PAR20 LED lamp
- Excellent color rendering
- Exceptional light distribution
- Enhanced passive cooling system allows for reduced junction temperatures, extending the life of the lamp
- Environmentally Friendly – No mercury, No lead & RoHS Compliant
- Maintenance free - Long life operation
- Integrated high efficiency driver
- Complies with ANSI standard PAR20 form factor
- All lamps are TÜV certified and tested to UL 1993, UL 8750 and are FCC certified
- No UV or IR radiation & No heat emitted in direction of light
- 5 year warranty

Specification Data

| CCT (K) | Beam Angle | Power (W) | Lumens (lm) | CBCP (cd) | Efficacy (lm/W) | CRI | Voltage | Base Type | Life (hrs) | Weight | Dimmable | Model No. |
|--------------------------|------------|-----------|-------------|-----------|-----------------|-----|------------------|-----------|------------|----------------|----------|----------------------|
| 2700K Incandescent White | 27° | 3.5 | 230 | 800 | 66 | 83 | 90-135 VAC, 60Hz | E26 | 50,000 | 6 oz (0.17 kg) | YES | LED-PAR20-35-1XD-INF |
| | | 5.9 | 372 | 1,300 | 63 | | | | | | | LED-PAR20-50-1XD-INF |
| | 35° | 3.5 | 215 | 506 | 61 | | | | | | | LED-PAR20-35-1XD-IF |
| | | 5.9 | 355 | 815 | 60 | | | | | | | LED-PAR20-50-1XD-IF |
| | 55° | 3.5 | 210 | 217 | 60 | | | | | | | LED-PAR20-35-1XD-IWF |
| | | 5.9 | 352 | 364 | 60 | | | | | | | LED-PAR20-50-1XD-IWF |
| 3000K Warm White | 27° | 3.5 | 230 | 800 | 66 | 83 | 90-135 VAC, 60Hz | E26 | 50,000 | 6 oz (0.17 kg) | YES | LED-PAR20-35-1WD-INF |
| | | 5.9 | 372 | 1,300 | 63 | | | | | | | LED-PAR20-50-1WD-INF |
| | 35° | 3.5 | 215 | 506 | 61 | | | | | | | LED-PAR20-35-1WD-IF |
| | | 5.9 | 355 | 815 | 60 | | | | | | | LED-PAR20-50-1WD-IF |
| | 55° | 3.5 | 210 | 217 | 60 | | | | | | | LED-PAR20-35-1WD-IWF |
| | | 5.9 | 352 | 364 | 60 | | | | | | | LED-PAR20-50-1WD-IWF |
| 4000K Cool White | 27° | 3.5 | 267 | 928 | 76 | 80 | 90-135 VAC, 60Hz | E26 | 50,000 | 6 oz (0.17 kg) | YES | LED-PAR20-35-1CD-INF |
| | | 5.9 | 432 | 1,508 | 73 | | | | | | | LED-PAR20-50-1CD-INF |
| | 35° | 3.5 | 249 | 587 | 71 | | | | | | | LED-PAR20-35-1CD-IF |
| | | 5.9 | 412 | 945 | 70 | | | | | | | LED-PAR20-50-1CD-IF |
| | 55° | 3.5 | 244 | 252 | 70 | | | | | | | LED-PAR20-35-1CD-IWF |
| | | 5.9 | 408 | 422 | 69 | | | | | | | LED-PAR20-50-1CD-IWF |

LEDnovation lamp models are tested for photometric performance in accredited third-party labs according to IES LM-79 requirements, with most reports available online at www.lednovation.com

DESIGNED AND MANUFACTURED IN NORTH AMERICA

TESTED TO:
UL1993 & UL8750



CERTIFICATION NUMBER:
UB 10 09 71814 003