

LED ROADWAY & AREA LIGHT



FIXTURE TYPE _____

JOB NAME _____

REP **HUDNUT LED LIGHTING**

PART NUMBER _____

SPECIFICATIONS

IP65 water resistant rated

UL listed

Type I and Type II beam spreads available

Modular design allows a wide range of light outputs

All aluminum housing

LED efficiencies are 150 Lm/W minimum

Operates in negative 40 to plus 122 degrees F. ambient air temp.

50,000 hour rated to 70% light output

3 year manufacturer warranty

CRI 75 minimum

72w = 22" L x 16" W x 5.25" D 5,400 lumens

145w = 31" L x 16" W x 5.25" D 10,800 lumens

220w = 37.5" L x 16" W x 5.25" D 16,500 lumens

Power factor >0.95

IES file and photometric report available

Maximum 2.44" O.D. pole fitter

ORDERING INFORMATION

<u>SERIES</u>	<u>LIGHT</u>	<u>BEAM</u>	<u>VOLTS</u>	<u>WATTS</u>	<u>MOUNTING</u>	<u>OPTIONS</u>
RWU-UN	3500K	TYPE I	100-240VAC	72w	PM = pole mount	PC = photo cell
	4500K	TYPE II	277VAC	145w		***
	6500K			220w		

NOTES

***Other options may be available. Contact Hudnut LED Lighting Solutions for additional information.

All values are nominal.

Product may differ slightly from photo

HUDNUT LED LIGHTING

11916 NE SUMNER STREET PORTLAND, OREGON 97220 503-233-8088 WWW.HUDNUT.COM INFO@HUDNUT.COM