

SLIM LINEAR SURFACE LED



FIXTURE TYPE _____

JOB NAME _____

REP **HUDNUT LED LIGHTING**

PART NUMBER _____

SPECIFICATIONS

Water resistant clear polycarbonate lens
 20" and 40" LED length individual bars
 45 foot candles on surface at 18" mounting with a single 20" bar
 Fully dimmable with dimmable power supply
 30,000 hour life to 70% output
 80+ CRI
 Capable of continuous rows with end to end sockets up to 16.5'
 Snap clips included to make installation simple

10" / 100+ lumen / 3 watt LED bar dimensions:
 Length = 9.9" Width = 0.7" Height = 0.5"
 20" / 200+ lumen / 5 watt LED bar dimensions:
 Length = 19.7" Width = 0.7" Height = 0.5"
 40" / 400+ lumen / 10 watt LED bar dimensions:
 Length = 39.4" Width = 0.7" Height = 0.5"
 1 year Hudnut warranty

ORDERING INFORMATION

<u>SERIES</u>	<u>LENGTH</u>	<u>LIGHT</u>	<u>BEAM</u>	<u>VOLTS</u>	<u>MOUNTING</u>	<u>OPTIONS</u>
SALF-QU	10"	30 = 3000K	120 = 120 deg.	12VDC****	SM = Surface	***
	20"	45 = 4500K****		24VDC		
	40"	50 = 5000K****				
		Red****				
		Green****				
		Blue****				
		RGB color change**** requires separate controller - call or email for information.				

NOTES

***Contact Hudnut LED Lighting Solutions for additional options and custom capabilities.

Products may differ slightly from photo. All values are nominal.

****SPECIAL ORDER ONLY

HUDNUT LED LIGHTING